

# PRECISION INSTRUMENT COMPANY

## Bi-metal Thermometers

### **B2Bx** 2" Dial Size Bimetal Thermometers

1/4" diameter, 1/4" NPT threaded stem

Plastic Lens

All Stainless Construction

With re-calibration screw on back of case

Accuracy: +/- 1 scale division

Available ranges: -40/160°F&C, 25/125°F, 0/220°F&C, 50/300°F&C, 50/500°F&C, 50/750°F

Available stem lengths: 2 1/2", 4" & 6" (others available upon request)



### **BxB5** 1" & 2" Dial Size Pocket Thermometers

Magnifying Plastic Lens

1/8" Diameter Pointed Plain Stem (Non-Threaded)

With Plastic Sleeve / Pocket Clip Case

Stainless Construction

With re-Calibration Feature

Accuracy: +/- 1 Scale Division

Available ranges: -40/160°F, 25/125°F&C, 0/220°F&C (or 'F only), 50/550°F&C (or 'F only)

Ranges for 2" Dial Size: -40/160°F&C, 0-220°F&C (others available upon request)

Stem Lengths: 5" (others available upon request)



### **B2Bx-x-CLIP** 2" Dial Size Clip Type Thermometers

Plastic Lens

1/8" Diameter Pointed Plain Stem (Non-Threaded)

With Stainless Steel Clip

All Stainless Construction

With re-calibration feature

Accuracy: +/- 1 scale division

Available range: 50/550°F&C (others available upon request)

Available stem lengths: 6", 10" or 12" (others available upon request)



### **B2B2-HW** 2" Dial Size Hot Water Thermometers

Plain Stem for use with Snap on Well\*

Plastic Lens

Aluminum Construction

Accuracy: +/- 1 scale division

Range: 30/240°F&C

Stem Length: 2 1/2"

\*Wells Available: Brass - 1/2" NPT Threaded or Solder Type



Note: not all ranges and stem lengths in stock, please call to check inventory